

AFRL-SR-BL-TR-98-

0570

REPORT DOCUMENTATION PAGE

28

data source,
app. 2 of this
1215 Jefferson

Public reporting burden for this collection of information is estimated to average 1 hour per gathering and maintaining the data needed, and completing and reviewing the collection of information, including suggestions for reducing this burden, to Washington Field Office, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Project, Suite 1204, Arlington, VA 22202-4302.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE		3. REPORT TYPE AND DATES COVERED Final 01 Jun 95 to 31 May 98	
4. TITLE AND SUBTITLE (AASERT -95) Graduate Student Research on Millimeter Wave Sources				5. FUNDING NUMBERS 61103D 3484/TS	
6. AUTHOR(S) Professor Gilgenbach				8. PERFORMING ORGANIZATION REPORT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) University of Michigan 3003 South State Street Ann Arbor, MI 48109-1274 Room 1058, Womersley Tower				10. SPONSORING/MONITORING AGENCY REPORT NUMBER F49620-95-1-0329	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) AFOSR/NE 110 Duncan Aven Room B115 Bolling AFB DC 20332-8050					
11. SUPPLEMENTARY NOTES					
12a. DISTRIBUTION/AVAILABILITY STATEMENT APPROVAL FOR PUBLIC RELEASE: DISTRIBUTION UNLIMITED				12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) During the period of the AASERT the graduate student completed experiments and a Ph. D. dissertation on microwave emission of large and small orbit rectangular cross section (RCS) gyrotron devices. Rectangular interaction cavities with both small orbit and large orbit axis encircling electron beams were used in gyrotron mechanisms to generate high power microwaves.					
14. SUBJECT TERMS				15. NUMBER OF PAGES	
				16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED		18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED		19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	
				20. LIMITATION OF ABSTRACT UL	

NSN 7540-01-280-5500

Standard Form 298 (Rev. 2-89)
Prescribed by ANSI Std. Z39-18

AUGMENTATION AWARDS FOR SCIENCE & ENGINEERING RESEARCH TRAINING
(AASERT)
REPORTING FORM

The Department of Defense (DoD) requires certain information to evaluate the effectiveness of the AASERT Program. By accepting this Grant which bestows the AASERT funds, the Grantee agrees to provide 1) a brief (not to exceed one page) narrative technical report of the research training activities of the AASERT-funded student(s) and 2) the information requested below. This information should be provided to the Government's technical point of contact by each annual anniversary of the AASERT award date.

1. Grantee identification data: (R&T and Grant numbers found on Page 1 of Grant)

a. University of Michigan
University Name

b. F49620-95-1-0329 c. 3484/TS
Grant Number R&T Number

d. Ronald M. Gilgenbach e. From: 1 June 95 To: 31 May 98
P.I. Name AASERT Reporting Period

NOTE: Grant to which AASERT award is attached is referred to hereafter as "Parent Agreement".

2. Total funding of the Parent Agreement and the number of full-time equivalent graduate students (FTEGS) supported by the Parent Agreement during the 12-month period prior to the AASERT award date.

a. Funding: \$ 221,897

b. Number FTEGS: 1

3. Total funding of the Parent Agreement and the number of FTEGS supported by the Parent Agreement during the current 12-month reporting period.

a. Funding: \$ 0 (ended June 14, 1995)

b. Number FTEGS 0

4. Total AASERT funding and the number of FTEGS and undergraduate students (UGS) supported by AASERT funds during the current 12-month reporting period.

a. Funding: \$ 113,510

b. Number FTEGS: 1

c. Number UGS: 0

19980813 012

VERIFICATION STATEMENT: I hereby verify that all students supported by the AASERT award are U.S. Citizens.

Ronald M. Gilgenbach
Ronald M. Gilgenbach
Principal Investigator

22 June 98
Date

Final Report for Augmentation Awards for Science and Engineering Research Training (AASERT)

Principal Investigator: Ronald M. Gilgenbach

Graduate Student: Jonathan M. Hochman

Nuclear Engineering and Radiological Sciences Department, University of Michigan

Grant Number: F49620-95-1-0329

Period Covered by Report: June 1 1995- May 31, 1998

During the period of the AASERT the graduate student completed experiments and a Ph. D. dissertation on microwave emission of large and small orbit rectangular cross section (RCS) gyrotron devices. Rectangular interaction cavities with both small orbit and large orbit axis encircling electron beams were used in gyrotron mechanisms to generate high power microwaves. The Michigan Electron Long Beam Accelerator (MELBA) produced an annular electron beam with e-beam parameters: $V = -0.7$ to -1.0 MV, $I_{diode} = 1-10$ kA, $I_{tube} = 0.1-3$ kA, and e-beam pulse length $= 0.4-1.0$ μ s. The small orbit e-beam was spun up into an axis encircling e-beam by passing it through a magnetic cusp prior to entering the RCS interaction cavity. The issues under investigation included polarization control of the microwave emission as a function of the interaction cavity magnetic field, microwave power as a function of pulse length, and mode competition. Along with microwave power measurements, cold tests utilizing a network analyzer were conducted, and frequency analysis was conducted with the use of a heterodyne mixer. Measurements of the optical emission of plasma in the RCS interaction cavity beam dump have also been completed.

Experimental results in the small orbit gyrotron demonstrated powers up to 23 MW in the horizontal polarization with little power measured in the vertical fundamental mode, and hence, polarization control was not obtained. Pulse shortening was observed in the small orbit gyrotron and power efficiency was typically less than 1%. Radiation darkening on glass showed that adiabatic compression of the e-beam produced a beam α (v_{\perp}/v_{\parallel}) of approximately 0.3 for the small orbit gyrotron. EGUN simulations agreed with these results, showing the e-beam's α to be between 0.2 and 0.3, increasing with the magnitude of adiabatic compression.

The large orbit gyrotron, operating at a lower current, produced much more successful results. Powers as high as 14 MW were measured in the fundamental TE_{101} mode at a frequency of 2.18 GHz, and 11 MW in the horizontally polarized TE_{011} mode at 2.85 GHz. The results showed a high degree of polarization [$P(TE_{101})/P(TE_{011}) = 1000$ or as low as $1/30$] as a function of cavity B-fields. The megawatt microwave output shifts from the fundamental TE_{101} mode to the TE_{011} mode as the B-field is raised from 1.5 to 1.9 kG. Efficiencies in the large orbit gyrotron were found to be as high as 8 %. Experimentally, the average e-beam α was approximately 1.0 at a magnetic field of 1.5 kG and rose to an average of approximately 1.3 for a B-field of 2 kG.

The highest power microwave pulses were on the order of 100 ns and demonstrated pulse shortening. Optical emission spectroscopy demonstrated the formation of hydrogen plasma in the cavity or output waveguide; these results imply that microwave pulse shortening could be related to this plasma produced by the e-beam dumping against the output waveguide walls.

To reduce mode competition, tapered cavities were introduced to replace the uniform RCS cavity. These experiments met with limited success. Cavity B, which was tapered in the vertical dimension to attempt suppression of the higher order, horizontally polarized TE_{01} mode, lowered the peak power in that mode to a peak value of 3 MW; furthermore, the mode frequency was shifted up from 2.85 GHz to above 3 GHz. This did not cause the power in the fundamental mode to increase, and tapering did not enhance the polarization ratio. Cavity C was tapered in the horizontal dimension to suppress the TE_{10} fundamental mode, and in this case the TE_{101} mode did not appear at 2.18 GHz. Either the TE_{01} mode dominated due to this taper, or the fundamental TE_{101} mode frequency shifted up to the frequency of the TE_{102} mode.

MAGIC code simulations (both 2D and 3D) predicted the ability to shift the linearly polarized output from the fundamental TE_{10} mode to the orthogonally polarized TE_{01} mode.